Coveya Ltd. St Ivel Way
Bristol BS30 8TY
T: 0800 915 9195
www.coveya.co.uk

High-Rise Telescopic Expressway Conveyor

A simple solution for efficient loading and unloading

The High-Rise Telescopic Expressway has been designed specifically as a cost-effective solution for efficient loading and unloading of shipping containers and trailers where no level loading dock is available.

Benefits:

- Significantly reduces time taken to load or unload loose loaded trailers and shipping containers.
- Has full penetration into any trailer or shipping container.
- Reduces number of personnel needed.
- Reduces risk of manual handling injury.
- Moves boxes quickly on free running PVC rollers utilizing heavy duty steel where needed to the load point.
- Makes the best use of gravity to move varying box weights at the right speed, all stands are fully adjustable using a winding handle.
- Connects to other Conveyors with the option of a drop-down end stop connector.
- High quality UK manufactured product, robust, long lasting, and simple to maintain. Fully welded construction powder coated in Coveya red.

The Telescopic range launched in 2020 builds on 30 years of development

- Ergonomically improved load and unload heights
- Our most robust construction ever throughout the range

Specification:

Telescopic extending gravity roller conveyor. High impact, low inertia, 50mm diameter PVC rollers mounted in fully welded mild steel channel frames powder coated blue BS4800 18-E-53. 50mm bright zinc plated mild steel rollers at load point and 20mm diameter bright zinc plated steel rollers at deck transfer sections. Conveyor mounted on heavy duty box section chassis and fitted with fixed and swivel braked castors. This system is supplied as a high-rise telescopic expressway with an additional 3.0m extension track. Skid plates are available to slow items on conveyor if required.

COVEYA

Coveya Ltd. St Ivel Way
Bristol BS30 8TY
T: 0800 915 9195
www.coveya.co.uk

Penetration Fully Extended	10,000mm into trailer or shipping container
Container/trailer floor height	1,300-1650mm
Conveyor load height above bed	900 – 1200mm – adjusted using screw jacks
Discharge height	1100 – 1450mm – adjusted using screw jacks
Rollers	50mm diameter high impact PVC
Roller load rating	20kg uniformly distributed
Conveyor load rating	50kg per linear metre
Overhanging loads	Yes, to 900mm wide over-all
Shortest item that will convey	225mm long
End stop plate	Yes
Length outside trailer/container	6500mm
Size when stored	One item 4500mm x 1100mm & one item 3100mm x 700mm

Load Point

Discharge Point

COVEYA

Coveya Ltd. St Ivel Way
Bristol BS30 8TY
T: 0800 915 9195
www.coveya.co.uk

THE CONVEYOR PEOPLE

COVEYA.CO.UK